

### Features

- Extremely low RMS phase jitter (random)
  - <1 ps (typical)
- Wide frequency range
  - 1 MHz to 220 MHz
  - 220 MHz to 800 MHz (contact SiTime)
- High frequency stability
  - $\pm 10$  PPM,  $\pm 15$  PPM,  $\pm 20$  PPM
  - $\pm 25$  PPM,  $\pm 50$  PPM
- Operating voltage
  - 1.8, 2.5 or 3.3 V
- Operating temperature range
  - Industrial, -40 to 85 °C
  - Extended Commercial, -20 to 70 °C
  - Commercial, 0 to 70 °C
- Small footprint
  - 5.0 x 3.2 x 0.85 mm
  - 7.0 x 5.0 x 0.85 mm
- Pb-free and ROHs compliant
- For Spread Spectrum see SiT9002
- Ultra-reliable start up and greater immunity from interference


### Benefits

- Ultra fast lead time: 2 to 3 weeks
- No crystal or capacitors required
- Eliminates crystal qualification time
- 50% + board saving space
- More cost effective than quartz oscillators, quartz crystals and clock ICs.
- Completely quartz-free


### Applications

- Server
- Router
- RAID controller
- Gigabit Ethernet
- 10 Gigabit Ethernet
- Fiber Channel
- SATA / SAS
- PCI-Express
- Fully Buffered DIMM
- System clock
- Networking and computing

### Block Diagram



### Pinout



## Pin Description

| Pin No. | Name  |        | Pin Description   |
|---------|-------|--------|---|
| 1       | ST/OE | Input  | Standby or Output Enable pin for OUT+ and OUT-.<br>OE:<br>When High or Open : OUT+ and OUT- = active<br>When Low : OUT+ and OUT- = High Impedance state<br>ST:<br>When High or Open : OUT+ and OUT- = active<br>When Low : OUT+ and OUT- = High Impedance State |
| 2       | NC    | NA     | Do Not connect pin, leave it floating.  |
| 3       | GND   | Power  | VDD power supply ground. Connect to Ground  |
| 4       | OUT+  | Output | 1 to 220 MHz programmable clock output .  |
| 5       | OUT-  | Output | 1 to 220 MHz programmable clock output .  |

## Absolute Maximum Ratings

Attempted operation outside the absolute maximum ratings of the part may cause permanent damage to the part. Actual performance of the IC is only guaranteed within the operational specifications, not at absolute maximum ratings.

### Absolute Maximum Table

| Parameter  | Min.      | Max.      | Unit  |
|--|-----------|-----------|-------|
| Storage Temperature  | -65       | 150       | °C    |
| VDD  | -0.5      | +4.00     | V     |
| Vin  | GND - 0.5 | VDD + 0.5 | V     |
| Theta JA ( with copper plane on VDD and GND) 5.0 x 3.2 package         | –         | 68        | °C/W  |
| 7.0 x 5.0 package when center pad is soldered down                     | –         | 38        | °C/W  |
| 7.0 x 5.0 package when center pad is not soldered down                 | –         | 90        | °C/W  |
| Theta JC (with PCB traces of 0.010 inch to all pins) 5.0 x 3.2 package | –         | 45        | °C/W  |
| 7.0 x 5.0 package when center pad is soldered down                     | –         | 35        | °C/W  |
| 7.0 x 5.0 package when center pad is not soldered down                 | –         | 48        | °C/W  |
| Soldering Temperature (follow standard Pb free soldering guidelines)   | –         | 260       | °C    |
| Number of Program Writes   | –         | 1         | NA    |
| Program Retention over -40 to 125C, Process, VDD (0 to 3.6V)           | –         | 1,000+    | years |
| Human Body Model (JESD22-A114)   | 2000      | –         | –     |
| Charged Device Model (JESD22-C101)                                     | 750       | –         | –     |
| Machine Model (JESD22-A115)  | 200       | –         | –     |

## Environmental Compliance

| Parameter                  | Condition/Test Method                           |
|----------------------------|---|
| Mechanical Shock           | MIL-STD-883F, Method 2002, 50 KG Shock          |
| Mechanical Vibration       | MIL-STD-883F, Method 2007, 70 G Vibration       |
| Temperature Cycle          | MIL-STD-883F, Method 1010-65-150°C (1000 cycle) |
| Solderability              | MIL-STD-883F, Method 2003                       |
| Moisture Sensibility Level | MSL1  |

## DC Electrical Specifications

LVC MOS input, OE or ST pin, 3.3V ±10% or 2.5V ±10% or 1.8V ±5%, -40 to 85°C

| Symbol          | Parameter          | Condition    | Min. | Typ. | Max. | Unit             |
|-----------------|--------------------|--------------|------|------|------|------------------|
| V <sub>IH</sub> | Input High Voltage |              | 70   | –    | –    | %V <sub>DD</sub> |
| V <sub>IL</sub> | Input Low Voltage  |              | –    | –    | 30   | %V <sub>DD</sub> |
| I <sub>IH</sub> | Input High Current | OE or ST pin | –    | –    | 10   | μA               |
| I <sub>IL</sub> | Input Low Current  | OE or ST pin | -10  | –    | –    | μA               |

LVPECL, 3.3V ±10% or 2.5V ±10%, -40 to 85°C

| Symbol             | Parameter                  | Condition   | Min.                 | Typ. | Max.                 | Unit |
|--------------------|----------------------------|---|----------------------|------|----------------------|------|
| V <sub>DD</sub>    | Supply Voltage             |   | 2.97                 | 3.3  | 3.63                 | V    |
|                    |                            |   | 2.25                 | 2.5  | 2.75                 | V    |
| I <sub>DD</sub>    | Supply Current             | V <sub>DD</sub> = 3.3, Excluding Load Termination Current | –                    | 75   | 84                   | mA   |
|                    |                            | V <sub>DD</sub> = 3.3, Excluding Load Termination Current | –                    | 75   | 84                   | mA   |
| V <sub>OH</sub>    | Output High Voltage        | 50 Ohm termination to V <sub>DD</sub> - 2.0V              | V <sub>DD</sub> -1.1 | –    | V <sub>DD</sub> -0.7 | V    |
| V <sub>OL</sub>    | Output Low Voltage         | See Figure 2, 3.  | V <sub>DD</sub> -2.0 | –    | V <sub>DD</sub> -1.4 | V    |
| V <sub>swing</sub> | Pk-Pk Output Voltage Swing |   | 600                  | 800  | 1000                 | mV   |

HCSL, 3.3V ±10% or 2.5V ±10%, -40 to 85°C

| Symbol             | Parameter                  | Condition   | Min. | Typ. | Max. | Unit |
|--------------------|----------------------------|---|------|------|------|------|
| V <sub>DD</sub>    | Supply Voltage             |   | 2.97 | 3.3  | 3.63 | V    |
|                    |                            |   | 2.25 | 2.5  | 2.75 | V    |
| I <sub>DD</sub>    | Supply Current             | V <sub>DD</sub> = 3.3, Excluding Load Termination Current | –    | 73   | 80   | mA   |
|                    |                            | V <sub>DD</sub> = 3.3, Excluding Load Termination Current | –    | 73   | 80   | mA   |
| V <sub>OH</sub>    | Output High Voltage        | 50 Ohm termination to GND                                 | 0.6  | 0.75 | 0.95 | V    |
| V <sub>OL</sub>    | Output Low Voltage         | See Figure 4.   | 0.0  | –    | 0.50 | V    |
| V <sub>swing</sub> | Pk-Pk Output Voltage Swing |   | 600  | 750  | 950  | mV   |

LVDS, 3.3V ±10% or 2.5V ±10%, -40 to 85°C

| Symbol            | Parameter                        | Condition   | Min. | Typ. | Max. | Unit |
|-------------------|----------------------------------|---|------|------|------|------|
| V <sub>DD</sub>   | Supply Voltage                   |   | 2.97 | 3.3  | 3.63 | V    |
|                   |                                  |   | 2.25 | 2.5  | 2.75 | V    |
| I <sub>DD</sub>   | Supply Current                   | V <sub>DD</sub> = 3.3, Excluding Load Termination Current | –    | 75   | 85   | mA   |
|                   |                                  | V <sub>DD</sub> = 3.3, Excluding Load Termination Current | –    | 70   | 77   | mA   |
| V <sub>OD1</sub>  | Differential Output Voltage      | Swing Mode = Normal                                       | 250  | 350  | 450  | mV   |
| ΔV <sub>OD1</sub> | V <sub>OD</sub> Magnitude Change | Single load termination.<br>See Figure 5.                 | –    | –    | 50   | mV   |
| V <sub>OS1</sub>  | Offset Voltage                   |   | –    | 1.2  | –    | V    |
| ΔV <sub>OS1</sub> | V <sub>OS</sub> Magnitude Change |   | –    | –    | 50   | mV   |
| V <sub>OD2</sub>  | Differential Output Voltage      | Swing Mode = High   | 500  | 700  | 900  | mV   |
| ΔV <sub>OD2</sub> | V <sub>OD</sub> Magnitude Change | Single load termination.<br>See Figure 5.                 | –    | –    | 50   | mV   |
| V <sub>OS2</sub>  | Offset Voltage                   |   | –    | 1.2  | –    | V    |
| ΔV <sub>OS2</sub> | V <sub>OS</sub> Magnitude Change |   | –    | –    | 50   | mV   |
| V <sub>OD3</sub>  | Differential Output Voltage      | Swing Mode = High   | 250  | 350  | 450  | mV   |
| ΔV <sub>OD3</sub> | V <sub>OD</sub> Magnitude Change | Double load termination.<br>See Figure 6.                 | –    | –    | 50   | mV   |
| V <sub>OS3</sub>  | Offset Voltage                   |   | –    | 1.2  | –    | V    |
| ΔV <sub>OS3</sub> | V <sub>OS</sub> Magnitude Change |   | –    | –    | 50   | mV   |

CML, 3.3V ±10% or 2.5V ±10% or 1.8V ±5%, -40 to 85°C

| Symbol              | Parameter                  | Condition   | Min.                               | Typ.                   | Max.                 | Unit |    |
|---------------------|----------------------------|---|------------------------------------|------------------------|----------------------|------|----|
| V <sub>DD</sub>     | Supply Voltage             |   | 2.97                               | 3.3                    | 3.63                 | V    |    |
|                     |                            |   | 2.25                               | 2.5                    | 2.75                 | V    |    |
|                     |                            |   | 1.71                               | 1.8                    | 1.89                 | V    |    |
| I <sub>DD</sub>     | Supply Current             | V <sub>DD</sub> = 3.3V  | Excluding Load Termination Current | –                      | 48                   | 51   | mA |
|                     |                            | V <sub>DD</sub> = 2.5V  |                                    | –                      | 48                   | 51   | mA |
|                     |                            | V <sub>DD</sub> = 1.8V  |                                    | –                      | 48                   | 51   | mA |
| V <sub>OH1</sub>    | Output High Voltage        | Swing Mode = Normal<br>Single Load Termination<br>See Figure 7. | V <sub>DD</sub> -0.1               | –                      | V <sub>DD</sub>      | V    |    |
| V <sub>OL1</sub>    | Output Low Voltage         |   | V <sub>DD</sub> -0.55              | V <sub>DD</sub> -0.425 | V <sub>DD</sub> -0.3 | V    |    |
| V <sub>swing1</sub> | Pk-PK Output Voltage Swing |   | 300                                | 425                    | 550                  | mV   |    |
| V <sub>OH2</sub>    | Output High Voltage        | Swing Mode = High<br>Single Load Termination<br>See Figure 7.   | V <sub>DD</sub> -0.1               | –                      | V <sub>DD</sub>      | V    |    |
| V <sub>OL2</sub>    | Output Low Voltage         |   | V <sub>DD</sub> -1.1               | V <sub>DD</sub> -0.85  | V <sub>DD</sub> -0.6 | V    |    |
| V <sub>swing2</sub> | Pk-PK Output Voltage Swing |   | 600                                | 850                    | 1100                 | mV   |    |
| V <sub>OH3</sub>    | Output High Voltage        | Swing Mode = High<br>Double Load Termination<br>See Figure 8.   | V <sub>DD</sub> -0.1               | –                      | V <sub>DD</sub>      | V    |    |
| V <sub>OL3</sub>    | Output Low Voltage         |   | V <sub>DD</sub> -0.55              | V <sub>DD</sub> -0.425 | V <sub>DD</sub> -0.3 | V    |    |
| V <sub>swing3</sub> | Pk-PK Output Voltage Swing |   | 300                                | 425                    | 550                  | mV   |    |

## AC Electrical Specifications

LVPECL, 3.3V ±10% , -40 to 85°C

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   |             | -50  | –    | +50  | PPM |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 100         | 150  | 300  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 106.25 MHz @ BW: 637 kHz to 10 MHz   | –           | 1.6  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz @ BW: 1.875 to 20 MHz   | –           | 0.5  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1 to 20 MHz  | –           | 0.7  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 106.25 MHz   | –           | 1.8  | 2.3  | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz   | –           | 1.3  | 1.8  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 1.3  | 1.8  | ps   |     |

LVPECL, 2.5V ±10% , -40 to 85°C

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   | -50         | –    | +50  | PPM  |     |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 100         | 150  | 300  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 106.25 MHz @ BW: 637 kHz to 10 MHz   | –           | 1.6  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz @ BW: 1.875 to 20 MHz   | –           | 0.5  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1 to 20 MHz  | –           | 0.7  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 106.25 MHz   | –           | 1.8  | 2.3  | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz   | –           | 1.3  | 1.8  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 1.3  | 1.8  | ps   |     |

HCSL, 3.3V ±10% , -40 to 85°C

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   |             | -50  | –    | +50  | PPM |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 200         | 280  | 375  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 100 MHz @ BW: 1.5 MHz to 22 MHz  | –           | 0.8  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1.5 MHz to 22 MHz  | –           | 0.4  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 100 MHz  | –           | 1.6  | 2.2  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 1.5  | 1.9  | ps   |     |

**HCSL, 2.5V ±10% , -40 to 85°C**

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   | -50         | –    | +50  | PPM  |     |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 200         | 300  | 400  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 100 MHz @ BW: 1.5 MHz to 22 MHz  | –           | 0.8  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1.5 MHz to 22 MHz  | –           | 0.4  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 100 MHz  | –           | 1.6  | 2.2  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 1.5  | 2.1  | ps   |     |

**LVDS, 3.3V ±10% , -40 to 85°C**

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 10          | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   | -50         | –    | +50  | PPM  |     |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 100         | 200  | 325  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 106.25 MHz @ BW: 637 kHz to 10 MHz   | –           | 1.7  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz @ BW: 1.875 to 20 MHz   | –           | 0.7  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1 to 20 MHz  | –           | 0.7  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 106.25 MHz   | –           | 2.0  | 2.7  | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz   | –           | 1.8  | 2.5  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 1.8  | 2.5  | ps   |     |

## LVDS, 2.5V ±10% , -40 to 85°C

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   | -50         | –    | +50  | PPM  |     |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 100         | 260  | 325  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 106.25 MHz @ BW: 637 kHz to 10 MHz   | –           | 1.7  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz @ BW: 1.875 to 20 MHz   | –           | 0.7  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1 to 20 MHz  | –           | 0.7  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 106.25 MHz   | –           | 2.5  | 3.3  | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz   | –           | 2.4  | 3.5  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 2.4  | 3.5  | ps   |     |

## CML, 3.3V ±10% , -40 to 85°C

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   | -50         | –    | +50  | PPM  |     |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 150         | 220  | 300  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 106.25 MHz @ BW: 637 kHz to 10 MHz   | –           | 1.6  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz @ BW: 1.875 to 20 MHz   | –           | 0.6  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1 to 20 MHz  | –           | 0.8  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 106.25 MHz   | –           | 2    | 2.5  | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz   | –           | 1.9  | 2.5  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 1.9  | 2.4  | ps   |     |

CML, 2.5V ± 10% , -40 to 85°C

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -10  | –    | +10  | PPM |
|                                |                           |   | -20 to 70°C | -15  | –    | +15  | PPM |
|                                |                           |   | -40 to 85°C | -20  | –    | +20  | PPM |
|                                |                           |   |             | -25  | –    | +25  | PPM |
|                                |                           |   | -50         | –    | +50  | PPM  |     |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 150         | 230  | 300  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 106.25 MHz @ BW: 637 kHz to 10 MHz   | –           | 1.6  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz @ BW: 1.875 to 20 MHz   | –           | 0.6  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1 to 20 MHz  | –           | 0.8  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 106.25 MHz   | –           | 2.1  | 2.5  | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz   | –           | 1.9  | 2.5  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 1.9  | 2.5  | ps   |     |

CML, 1.8V ± 5% , -40 to 85°C

| Symbol                         | Parameter                 | Condition   | Min.        | Typ. | Max. | Unit |     |
|--------------------------------|---------------------------|---|-------------|------|------|------|-----|
| F <sub>out</sub>               | Output Frequency          |   | 1.0         | –    | 220  | MHz  |     |
| F <sub>sta</sub>               | Frequency Stability       | Inclusive of initial tolerance, operating temp., rated power supply voltage change, load change | 0 to 70°C   | -15  | –    | +15  | PPM |
|                                |                           |   | -20 to 70°C | -20  | –    | +20  | PPM |
|                                |                           |   | -40 to 85°C | -25  | –    | +25  | PPM |
|                                |                           |   |             | -50  | –    | +50  | PPM |
| F <sub>age</sub>               | Aging                     | First year @ 25°C   | –           | –    | 1    | PPM  |     |
| DC                             | Duty Cycle                |   | 45          | –    | 55   | %    |     |
| t <sub>R</sub> /t <sub>F</sub> | Output Rise/Fall Time     | 20% to 80%  | 150         | 240  | 325  | ps   |     |
| PH <sub>J</sub>                | RMS Phase Jitter (random) | F <sub>out</sub> = 106.25 MHz @ BW: 637 kHz to 10 MHz   | –           | 1.7  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz @ BW: 1.87 to 20 MHz  | –           | 0.6  | –    | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz @ BW: 1 to 20 MHz  | –           | 0.8  | –    | ps   |     |
| P <sub>J</sub>                 | RMS Period Jitter         | F <sub>out</sub> = 106.25 MHz   | –           | 2.3  | 2.9  | ps   |     |
|                                |                           | F <sub>out</sub> = 156.25 MHz   | –           | 2.1  | 2.7  | ps   |     |
|                                |                           | F <sub>out</sub> = 200 MHz  | –           | 2.1  | 2.7  | ps   |     |

Termination Diagrams




Figure 1. LVPECL AC Coupled Typical Termination




Figure 2. LVPECL DC Coupled Typical Termination with Termination Voltage




Figure 3. LVPECL DC Coupled Typical Termination without Termination Voltage




Figure 4. HCSL Typical Termination

**Note:**

1. All the tests are done with  $R_S = 20 \text{ Ohm}$  (recommended).





Figure 5. LVDS Single Termination (Load Terminated)



*Note: For AC coupled operation, include/insert decoupling caps at points A or B*

Figure 6. LVDS Double Termination (Source + Load Terminated)





Figure 7. CML Single Load Termination




- Notes:
1. For DC-coupled operation,  $VT1 = VT2$
  2. For AC coupled operation, include/insert decoupling caps at points A or B
  2. For AC-coupled operation with capacitors placed at point A,  $VT2$  sets the input common mode of Receiver Device and need not to be related to  $VT1$

Figure 8. CML Double Load Termination

**Ordering Information**

**SiT9102AC-132N33E123.12345T**




| Frequency Stability | Temperature Range         |                    |                    |
|---------------------|---------------------------|--------------------|--------------------|
|                     | N = 0 to 70C              | C = -20 to 70C     | I = -40 to 85C     |
| ± 10 PPM            | VDD = 3.3 or 2.5 V        | NA                 | NA                 |
| ± 15 PPM            | VDD = 1.8 or 2.5 or 3.3 V | VDD = 2.5 or 3.3 V | VDD = 2.5 or 3.3 V |
| ± 20 PPM            | NA                        | All VDDs           |                    |
| ± 25 PPM            | NA                        |                    |                    |
| ± 50 PPM            | NA                        |                    |                    |

Package Information [1]

Dimension (mm)

Land Pattern [2] (recommended) (mm)


**5.0 x 3.2 x 0.85mm**



Notes:

1. xxxx top marking denotes manufacturing lot number.
2. A capacitor of value 0.1µF between VDD and GND is recommended

**7.0 x 5.0 x 0.85mm**



© SiTime Corporation 2008. The information contained herein is subject to change at any time without notice. SiTime assumes no responsibility or liability for any loss, damage or defect of a Product which is caused in whole or in part by (i) use of any circuitry other than circuitry embodied in a SiTime product, (ii) misuse or abuse including static discharge, neglect or accident, (iii) unauthorized modification or repairs which have been soldered or altered during assembly and are not capable of being tested by SiTime under its normal test conditions, or (iv) improper installation, storage, handling, warehousing or transportation, or (v) being subjected to unusual physical, thermal, or electrical stress.

**Disclaimer:** SiTime makes no warranty of any kind, express or implied, with regard to this material, and specifically disclaims any and all express or implied warranties, either in fact or by operation of law, statutory or otherwise, including the implied warranties of merchantability and fitness for use or a particular purpose, and any implied warranty arising from course of dealing or usage of trade, as well as any common-law duties relating to accuracy or lack of negligence, with respect to this material, any SiTime product and any product documentation. Products sold by SiTime are not suitable or intended to be used in a life support application or component, to operate nuclear facilities, or in other mission critical applications where human life may be involved or at stake. All sales are made conditioned upon compliance with the critical uses policy set forth below.

**CRITICAL USE EXCLUSION POLICY**  
 BUYER AGREES NOT TO USE SITIME'S PRODUCTS FOR ANY APPLICATION OR IN ANY COMPONENTS USED IN LIFE SUPPORT DEVICES OR TO OPERATE NUCLEAR FACILITIES OR FOR USE IN OTHER MISSION-CRITICAL APPLICATIONS OR COMPONENTS WHERE HUMAN LIFE OR PROPERTY MAY BE AT STAKE.

SiTime owns all rights, title and interest to the intellectual property related to SiTime's products, including any software, firmware, copyright, patent, or trademark. The sale of SiTime products does not convey or imply any license under patent or other rights. SiTime retains the copyright and trademark rights in all documents, catalogs and plans supplied pursuant to or ancillary to the sale of products or services by SiTime. Unless otherwise agreed to in writing by SiTime, any reproduction, modification, translation, compilation, or representation of this material shall be strictly prohibited.