	Title:	Performance Report SiT1602B, 4.096MHz			
	Type:	Performance report	Rev:	1.0	
	Orig:		Date:	Apr 10, 2014	

This report contains sample performance data for SiT1602B-4.096MHz.

Conditions:

- Frequency 4.096 MHz
- Vdd 1.8V, 2.5V, 2.8V, 3.0V, 3.3V
- Temperature 25 °C
- Termination:
 - o No load for IDD
 - o 50Ω to GND for phase noise
 - o 15pF for other tests

Equipment:


- Agilent DSA90604 oscilloscope (6GHz, 20Gsps)
 - o Period jitter, waveform, rise/fall time, duty cycle, amplitude
- Agilent E5052B Signal Source Analyzer
 - o Phase noise, integrated phase jitter
- Power supply current
 - o Agilent 34401A DMM

Data:

- Period Jitter, Duty cycle, Rise/Fall time, Amplitude, Idd
- Output waveforms
- Frequency stability versus temperature

Table 1. Performance data

Parameter	Units	Voltage				
		1.8 V	2.5 V	2.8 V	3.0 V	3.3 V
Period jitter	ps, rms	2.26	2.03	1.95	2.01	1.96
Period jitter (10,000 cycles)	ps, pk-pk	17.0	15.4	15.1	14.6	14.9
Duty cycle	%	50.0	50.0	50.0	50.0	50.1
Rise time (20% - 80%)	ns	1.26	1.03	0.94	0.99	0.93
Fall time (80% - 20%)	ns	1.26	0.99	0.90	0.97	0.92
Amplitude	V	1.80	2.50	2.79	3.02	3.30
Current consumption (no load, output enabled)	mA	3.33	3.39	3.42	3.43	3.46
Current consumption (no load, output disabled)	mA	3.35	3.42	3.47	3.52	3.59

	Title:	Performance Report SiT1602B, 4.096MHz		
	Type:	Performance report	Rev:	1.0
	Orig:		Date:	Apr 10, 2014





Figure 1. Duty cycle, Rise/Fall time and Amplitude 1.8V

	Title:	Performance Report SiT1602B, 4.096MHz		
	Type:	Performance report	Rev:	1.0
	Orig:		Date:	Apr 10, 2014





Figure 2. Duty cycle, Rise/Fall time and Amplitude 2.5V

The information contained in this document is confidential and proprietary to SiTime Corporation. Unauthorized reproduction or distribution is prohibited.

	Title:	Performance Report SiT1602B, 4.096MHz		
	Type:	Performance report	Rev:	1.0
	Orig:		Date:	Apr 10, 2014





Figure 3. Duty cycle, Rise/Fall time and Amplitude 2.8V

The information contained in this document is confidential and proprietary to SiTime Corporation. Unauthorized reproduction or distribution is prohibited.

	Title:	Performance Report SiT1602B, 4.096MHz	
	Type:	Performance report	Rev: 1.0
	Orig:		Date: Apr 10, 2014





Figure 4. Duty cycle, Rise/Fall time and Amplitude 3.0V

	Title:	Performance Report SiT1602B, 4.096MHz	
	Type:	Performance report	Rev: 1.0
	Orig:		Date: Apr 10, 2014




Figure 5. Duty cycle, Rise/Fall time and Amplitude 3.3V

SiTime™	Title:	Performance Report SiT1602B, 4.096MHz		
	Type:	Performance report	Rev:	1.0
	Orig:		Date:	Apr 10, 2014



Figure 6. Frequency stability* versus temperature, 1.8 V

*Please note that frequency stability in SiTime devices is not depended on output frequency.

SiTime™	Title:	Performance Report SiT1602B, 4.096MHz		
	Type:	Performance report	Rev:	1.0
	Orig:		Date:	Apr 10, 2014



Figure 7. Frequency stability versus temperature, 2.5 V

The information contained in this document is confidential and proprietary to SiTime Corporation. Unauthorized reproduction or distribution is prohibited.


	Title:	Performance Report SiT1602B, 4.096MHz		
	Type:	Performance report	Rev:	1.0
	Orig:		Date:	Apr 10, 2014



Figure 8. Frequency stability versus temperature, 2.8 V

The information contained in this document is confidential and proprietary to SiTime Corporation. Unauthorized reproduction or distribution is prohibited.


	Title:	Performance Report SiT1602B, 4.096MHz	
	Type:	Performance report	Rev: 1.0
	Orig:		Date: Apr 10, 2014



Figure 9. Frequency stability versus temperature, 3.0 V

The information contained in this document is confidential and proprietary to SiTime Corporation. Unauthorized reproduction or distribution is prohibited.


	Title:	Performance Report SiT1602B, 4.096MHz		
	Type:	Performance report	Rev:	1.0
	Orig:		Date:	Apr 10, 2014



Figure 10. Frequency stability versus temperature, 3.3 V

The information contained in this document is confidential and proprietary to SiTime Corporation. Unauthorized reproduction or distribution is prohibited.