

## SiT8924B-13-0009

### Description

This datasheet addendum defines the configuration of custom part number SiT8924B-13-0009, which is a configuration-specific version of the SiTime base SiT8924 datasheet. Please refer to the SiT8924 datasheet and related collateral for further information about this device. You can search for and download the base SiT8924 datasheet from the SiTime website. Go to <https://www.sitime.com/datasheet/sit8924> for more information.

### Configuration Information

Custom Part Number: SiT8924B-13-0009

Base Part Number: SiT8924

Silicon Revision: B

Frequency (MHz): 27.000000

Frequency Stability (PPM):  $\pm 50$

Temperature Range ( $^{\circ}\text{C}$ ): -40 to 125

Output Drive Strength: R

Supply Voltage (V): 1.8

Package Size (mm): 2.5x2.0

Feature Pin: OE

Packaging Options (Append to the end of the custom part number when ordering. For example, order SiT8924B-13-0009D for a 8 mm Tape & Reel, 3ku Reel):

- "D": 8 mm Tape & Reel, 3ku Reel
- "E": 8 mm Tape & Reel, 1ku Reel
- "": (blank) Bulk for sampling only

## Revision History

### Revision: 1

- Revision Date: 04/24/2020
- Initial Release

## Corporate Headquarters

SiTime Corporation  
5451 Patrick Henry Drive  
Santa Clara, CA 95054, USA

## Contact Information

For further information on a product, technology, document, or to locate your nearest sales office, please visit:

<https://www.sitime.com>

Phone: +1-408-328-4400

FAX: +1-408-328-4439

## Notice

© SiTime Corporation 2020. The information contained herein is subject to change at any time without notice. SiTime assumes no responsibility or liability for any loss, damage or defect of a Product which is caused in whole or in part by (i) use of any circuitry other than circuitry embodied in a SiTime product, (ii) misuse or abuse including static discharge, neglect or accident, (iii) unauthorized modification or repairs which have been soldered or altered during assembly and are not capable of being tested by SiTime under its normal test conditions, or (iv) improper installation, storage, handling, warehousing or transportation, or (v) being subjected to unusual physical, thermal, or electrical stress.

Disclaimer: SiTime makes no warranty of any kind, express or implied, with regard to this material, and specifically disclaims any and all express or implied warranties, either in fact or by operation of law, statutory or otherwise, including the implied warranties of merchantability and fitness for use or a particular purpose, and any implied warranty arising from course of dealing or usage of trade, as well as any common-law duties relating to accuracy or lack of negligence, with respect to this material, any SiTime product and any product documentation. Products sold by SiTime are not suitable or intended to be used in a life support application or component, to operate nuclear facilities, or in other mission critical applications where human life may be involved or at stake. All sales are made conditioned upon compliance with the critical uses policy set forth below.

### CRITICAL USE EXCLUSION POLICY

BUYER AGREES NOT TO USE SITIME'S PRODUCTS FOR ANY APPLICATION OR IN ANY COMPONENTS USED IN LIFE SUPPORT DEVICES OR TO OPERATE NUCLEAR FACILITIES OR FOR USE IN OTHER MISSION-CRITICAL APPLICATIONS OR COMPONENTS WHERE HUMAN LIFE OR PROPERTY MAY BE AT STAKE.

SiTime owns all rights, title and interest to the intellectual property related to SiTime's products, including any software, firmware, copyright, patent, or trademark. The sale of SiTime products does not convey or imply any license under patent or other rights. SiTime retains the copyright and trademark rights in all documents, catalogs and plans supplied pursuant to or ancillary to the sale of products or services by SiTime. Unless otherwise agreed to in writing by SiTime, any reproduction, modification, translation, compilation, or representation of this material shall be strictly prohibited.